

CP-A200 Features and Benefits

HITACHI
Inspire the Next



3,000 ANSI lumens	Bright and clear images in any medium size venue.
Ultra Short Throw lens	The Hitachi CP-A200 features an Ultra Short Throw lens which will project a 60" image at 1.4 feet. This not only prevents obstructions but also means no shadows and no light shinning in the presenter's eyes.
Perfect Fit 2*	Perfect fit 2 enables the user to adjust the four corners and sides of the image one by one. Perfect Fit 2 provides vertical and horizontal digital correction of either barrel or pin cushion distortions. This feature helps correct geometric and complicated distortions. Perfect Fit 2 allows the projected image to fit correctly to the screen quickly and easily.
Hybrid Filter (2,000 Hours between maintenance)	The Hitachi CP-A200 projector provides users with a lower total cost of ownership by offering easier and less frequent maintenance.
Lamp life approximately 3,000 Hours (Whisper Mode)**	Another key to low total cost of ownership is a long life lamp. The CP-A200 lamp is rated at 2,000 hours in standard mode and 3,000 hours in Eco Mode.
7 watt Audio Output	7W audio output eliminates the need to connect external speakers.
Audio Pass Through	The projector can output audio in stand-by mode, allowing you to listen to external speakers via the projector's audio output. Keeping the projector in standby mode saves lamp life.
Power Saving Mode	The Saving mode reduces the stand-by power consumption to 5W with limitation of some features.
Lamp door on Top	Easy maintenance is another attractive function of the CP-A200, as its lamp door is on top of the model.
White Board Mode	Limits the peak white by changing the gamma curve limiting its brightness when used with a whiteboard to protect the eye health of teachers and students. Exclusive to Hitachi.
Input source naming	Users can name input sources in simple language instead of factory default name. Exclusive to Hitachi.
IR remote Frequency Change	To avoid conflict with fluorescent lights or IrDA (IR signal) from notebook PC, the frequency of the IR remote control can be changed from the menu. Exclusive to Hitachi.
Template Function	Line templates in the projector menu can help when writing on a whiteboard. There are four types of line templates to choose from. Exclusive to Hitachi.
MyButton / MySource	There are 2 customizable buttons on the remote control that users can program to execute any projector command such as: Direct input (RGB1, S-video etc.), Picture Mode, Filter Reset. My source adds a third source button labeled document camera for quick access to another important teaching tool.
PIN Lock/ MyScreen PIN Lock/ MyText	PIN lock protection can limit projector users. MyScreen PIN Lock keeps captured images on the startup screen. Users can set a school's name or company's logo to "MyScreen" clearly identifying ownership. MyText provides the ability to write text on the start up screen. Example, model name, serial number, or location.
Serial Number Label on Side	It is convenient for users or auditors to be able to check the model name and serial number of an asset easily when the product is ceiling mounted. The label is upside-down and easily viewable for ceiling-use. Exclusive to Hitachi.
Closed captioning	CC1, CC2, CC3, CC4

*Not all geometric shapes are supported

** Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.