

Key Features

- 2,500 ANSI Lumens
- Native XGA Resolution
- 1.7 kg.
- 1 RGB Input / Composite / S-Video
- PC-less presentation
- 1W speaker output
- Lamp door on the top
- Approx. 3,000 hrs. (whisper Mode)
- 29 dB (Whisper Mode)
- Transition Detector



Specifications

Model Name	CPX5 Series
Liquid Crystal Panel Structure	0.63" polysilicon active-matrix TFT x 3
Number of Pixels	786,432 pixels
Resolution	540 TV lines
	1024 dots X 768 lines
Colors	16.7 million colors
Aspect Ratio	Native 4:3/16:9 compatible
Lens	F1.8 - 1.9, manual zoom x 1.2
Throw Ratio (distance : width)	1.3 - 1.5 : 1
Lamp	190W UHB
Brightness	2,500 ANSI Lumens
Expected lamp Life	Approximately 2,000 hours (normal) 3,000 hours (whisper)
Contrast Ratio	500 : 1
Speaker Output	1W (1 speaker)
Power Supply	AC100 - 120V / AC220 - 240V 50/60 Hz Power
Power Consumption	310W
Operating Temperature	5°C - 35°C (41°F - 95°F)
Input Signals	RGB
	Composite Video
	Component Video
Acoustic Noise Level	40 dB (33 dB in whisper mode)
H-Sync	15 kHz - 106 kHz
V-Sync	50 kHz - 120 kHz
Vertical Keystone	+ / - 30°
Approvals	UL60950 / C-UL, FCC Part15, Class B, EN60950, C-Tick
RGB Input	Analog RGB
RGB Output	RGB
Video Input	S-Video
	Composite Video
	Component Video
Audio	Input
	Output
Control Terminals	---
Other	USB Memory Reader
Dimensions (W x H x D)	274 x 59 x 205mm
Weight	1.7 kg.
Additional Features	Kensington Slot, MyMemory / MyScreen / MyButtons, Digital Gamma Correction, Whiteboard/Blackboard Mode, Input Source Naming
Supplied Accessories	Remote Control, Batteries (AA), RGB cable, RCA Video Cable, Power Cord, Multiple language operator / Safety Manual, Soft Case, Security Label
Lamp	DT00821
Remote Control	HL02224
Filter	MU03602

Screen Size 4:3 Throw Distance

Diagonal*	Width*	Min*	Max*
30	24	30	36
60	48	61	73
80	64	81	97
100	80	102	122
120	96	122	147
150	120	153	183
200	160	204	245
300	240	306	368

Throw Ratio: 1.3 - 1.5:1 (distance : width)
*Measured in inches

